

KÄRCHER

makes a difference



RUGGED AND POWERFUL CLEANING POWER.

Roll cage, gas/diesel-powered, cold water pressure washers.

PROFESSIONAL | HD PB/DB CAGE

HD PB/DB CAGE



Extra rugged and powerful.

Our roll cage models are the most powerful units in our cold water line, with cleaning power of up to 5000 PSI. Protected by a rugged powder coated roll cage built of 1-1/4" steel, the PB Cage units feature powerful Vanguard, Honda or Kohler engines, tri-plunger oil bath Kärcher pumps, flat-free tires, and an extra rugged belt-drive assembly with notched V belts and cast iron pulleys. All single and double-axle models are ETL safety certified.



1 Powerful and durable

- Safety thermal pump saver valve protects against hot-water damage by venting recirculated water.
- Rugged roll cage and chassis made of 1 1/4-inch steel and powder coated with an epoxy finish for all-weather protection.
- Reliable Honda, Vanguard or Lombardini engines with 2-year warranty; low-oil alert and silent-tone muffler.
- Industrial-grade, tri-plunger, oil-bath Kärcher high pressure pump with forged brass head and ceramic pistons; backed by 7-year warranty.
- Notched V-belts and cast-iron pulleys reduce belt slippage and provide longer pump life.
- 50' durable wire-braid hose rated for 3000 or 5000 PSI; with hose guard for burst protection
- Inlet strainer protects pump from debris in the water source.

2 Smart features

- Five conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Totally enclosed, OSHA-compliant, high-impact polyethylene belt guard and easy-to-adjust belt tension device.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

3 Outstanding mobility

- Heavy-duty lifting beam for ease in loading and transporting.
- 13" tubed pneumatic tires with steel rims for easy maneuvering on all terrains and to absorb vibration.

TECHNICAL DATA AND EQUIPMENT

Features

- Belt-drive
- Rugged steel chassis & roll cage
- Honda, Vanguard or Kohler engine
- Cleaning power up to 5000 PSI
- Electric start on dual-axle models*
- Industrial belt-drive Kärcher pump with 7-year warranty
- Flat-free tires

Technical data

Model	Part No.	GPM	PSI	Drive	CC	Engine	Fuel	Pump	Ship Weight (lbs.)	Ship Dimensions (L x W x H) inches
HD 3.7/35 PB Cage	1.575-205.0	3.7	3500	Belt	389	Honda GX390	Gas	Kärcher KM	350	42 x 26 x 30
HD 4.0/40 PB Cage	1.575-207.0	4.0	4000	Belt	479	Vanguard 16	Gas	Kärcher KT	470	42 x 26 x 30
HD 4.0/50 PeB Cage*	1.575-200.0	4.0	5000	Belt	688	Honda GX630	Gas	Kärcher KX	495	42 x 26 x 30
HD 4.5/50 PeB Cage*	1.575-201.0	4.5	5000	Belt	688	Honda GX660	Gas	Kärcher KX	500	42 x 26 x 30

Options (field installed)

Order No.	Description
9.801-028.0	100' EZEE Hose Reel kit, single axle (hose not included)
9.801-029.0	100' Hose Reel kit, 5000 psi, double axle (hose not included)

Please contact us for more information:

North America

4555 Airport Way
Denver, CO 80239
U.S.A.

Phone 888-805-9852
Fax 800-248-8409

www.karcher.com/us

Canada

6535 Millcreek Drive
Unit 67
Mississauga, ON L5N 2M2
Canada

Phone 905-672-8233
Fax 905-672-3155

www.karcher.ca